




1.2" 2.4/16mm C		1.2"	1.1"	1"
FOCAL LENGTH		f=16mm		
F-NUMBER		F=1:2.4,2.8,4,5.6,8		
PICTURE SIZE		11.5x15.4mm	10.6x14.1mm	9.6x12.8mm
ANGLE OF VIEW (∞)	VER. ANGLE	40.0°	37.0°	33.7°
	HOR. ANGLE	52.4°	48.4°	44.3°
	DIA. ANGLE	63.2°	58.9°	54.2°
DISTORTION (TV)		-0.6%		
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	371mm	341mm	308mm
	HOR.	501mm	458mm	414mm
	DIA.	627mm	575mm	522mm
MINIMUM FOCUS DISTANCE		0.5m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		19.57mm in air		
FILTER SCREW SIZE		M34.0x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT φ20.2mm		REAR φ16.6mm
MOUNT		C-MOUNT		
EXIT PUPIL		-65.0mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 200lp/mm		CORNER 125lp/mm
WEIGHT		95 g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺 度	1/1	工場番号	LM16EC-IR
		機種名	1.2" F2.4 f=16mm		
2024.08.28	寸法修正	機種番	LM16EC-IR 外観図		
2024.08.01	作成年月日				